


Easi-Heat Plus 25C-29C


High efficiency combi boiler

	Automatic Modulation		5 Year Warranty
	25C	29C	


EASI-HEAT PLUS

HIGH EFFICIENCY COMBI BOILER

The Vokèra Easi-Heat Plus is an extremely compact and versatile combination boiler that offers flexible installation. Its small dimensions allow for kitchen cupboard fit and the boiler can be easily converted to LPG via an optional kit. For peace of mind, Easi-Heat Plus comes with a 5 year warranty⁽¹⁾ as standard and is Class A efficiency for both space and water heating under ErP.



- Flue gas analysis test point
- Cyclonic separator
- Premix burner
- Expansion vessel location allows for easy servicing maintenance
- Aluminium heat exchanger
- High efficiency pump
- DHW plate heat exchanger
- Electric insulation IPX5D
- Frost protection via PCB



EASI-HEAT PLUS

HIGH EFFICIENCY COMBI BOILER

Fully compliant with the Energy-related Products directive.

5 year parts and labour warranty.⁽¹⁾

Compact dimensions and low lift weight enable a flexible installation with the boiler able to be sited almost anywhere in the home, including a kitchen cupboard.

Designed for easy installation. Standard Vokèra pipework layout enables trouble-free replacement of older Vokèra models.

Hot water survivor function: If the hot water thermistor fails it will use the primary thermistor to provide hot water at 55°C to ensure the end-user has access to a supply of warm water.

Simple commissioning, only minimal adjustments are required after installation and automatic modulation eliminates the need to range rate the boiler.

Built-in mechanical time clock.

Anti-cycling control prevents energy wasteful on/off cycling and reduces wear and tear.

Low NOx - Class 5 performance.

Built-in frost protection, protects the appliance from damage during periods of cold weather.

Plated heat exchanger reduces the risk of scaling and comes with 5 year anti-scale warranty.

Installation time saving features: Built-in condense trap with safety device and push-fit connection.

Combustion analysis test point for easy servicing and maintenance.

Can be converted to LPG.

Individual heating and hot water controls ensure a simple temperature adjustment operation for the end user.

^{*}Including clock tray

⁽¹⁾Subject to registration and annual service.

SPECIFICATION	EASI-HEAT PLUS 25C	EASI-HEAT PLUS 29C
PRODUCT ORDER CODE	20116909	20116910
CENTRAL HEATING		
HEAT INPUT (kW)	20	25
MAXIMUM HEAT OUTPUT @ 80°C/60°C (kW)	19.5	24.5
DOMESTIC HOT WATER		
MAXIMUM INPUT (kW)	25	29
FLOW RATE - 35°C RISE (L/MIN)	10.2	12
DIMENSIONS		
HEIGHT (MM)*	795	795
WIDTH (MM)	405	405
DEPTH (MM)	248	248
WEIGHT		
DRY WEIGHT (KG)	28	29
CONNECTIONS		
FLOW & RETURN	22mm	22mm
GAS	15mm	15mm
DHW INLET & OUTLET	15mm	15mm
SAFETY VALVE	15mm	15mm
CONDENSATE	21mm	21mm
FLUE DETAILS		
MAXIMUM HORIZONTAL FLUE LENGTH (60/100MM)	5.85m	4.85m
MAXIMUM VERTICAL FLUE LENGTH (60/100MM)	6.85m	5.85m
MAXIMUM HORIZONTAL FLUE LENGTH (80/125MM)	15.3m	12.8m
MAXIMUM VERTICAL FLUE LENGTH (80/125MM)	20.3m	17.8m
ELECTRICAL DATA		
VOLTAGE (V/Hz)	230/50	230/50
EFFICIENCY		
ERP SEASONAL SPACE HEATING ENERGY EFFICIENCY (CLASS/%)	A/93	A/93
ERP WATER HEATING EFFICIENCY (XL PROFILE) (CLASS/%)	A/85	A/84
SAP 2009 EFFICIENCY (%)	89.1	89.0
NOX CLASS	5	5



Registered address:

Vokèra Limited
Borderlake House
Unit 7 Riverside Industrial Estate
London Colney
Herts AL2 1HG

enquiries@vokera.co.uk
www.vokera.co.uk

Sales, General Enquiries:

T 0844 391 0999
F 0844 391 0998



© 2016 Vokèra Limited.
We reserve the right to change specification without prior notice.
Consumers statutory rights are not affected.
All rights reserved. E&OE.

A Riello Group Company. Company Reg No: 1047779

Issue 02/16/NP